
GENERAL INFORMATION OF QUY NHON PORT

(Updated Aug 2024)

Disclaimer: The information below is supplied by Quynhon Port Authority, Quy Nhon Port and authorities concerned. While great efforts have been made to maintain the information as accurate and timely-updated as possible, MINH LONG MSC takes no liability or responsibility for any errors, inaccuracies, or omissions in the content herein.

1. Geographical Nature:

1.1. Port Condition:	International sea port
1.2. Position:	Latitude: 13°46'33" N Longitude: 109°15'00" E
1.3. Tidal regime:	Irregular semi-diurnal. Max tide: 2.2m. Min tide: 0.5m. Average fluctuation: 2.0m. Max drafts: F/9.00m A/9.50 m (with tide) with 0.50m trim. UKC : 1.0m
1.4. Channel:	Length: 9km. Depth: -11m. Width: 110m. One-way operation. Channel is equipped with light-buoys (13 buoys) and leading marks.
1.5. Weather:	Sunny season: January to late September. Raining season: October to late December

2. Navigational Regulations:

2.1. Pilot Station:	Latitude: 13°44'18" N Longitude: 109°15'18" E
2.2. Anchorage:	Within Rectangular (WGS84); P1(13°44'32" N; 109°15'00" E), P2 (13°44'37.5" N; 109°15'29" E), P3 (13°43'33" N; 109°15'42" E), P4 (13°43'28" N; 109°15'12" E)
2.3. Pilotage:	Compulsory for GRT ≥ 2,000mt.
2.4. Communication:	Port Control: VHF CH16 - Pilot: VHF CH12
2.5. Tugboat Service:	Compulsory for all vessels with LOA ≥ 80m. Exemption for vessels with a bow thruster might be granted by Port Authority on a case-by-case basis. Total 07 tugboats with power range from 800HP to 4059HP
2.6. Restrictions:	- Airdraft: Nil - Beam: Nil - Draft: F/8.7m and A/9.0m (min trim 0.5m) - LOA: Less than 200m - DWT: Less than 30,000mt DWT. Vessel of more than 30,000mt must have special permit from Port Authority on a case-by-case basis.

3. Port Operations:

3.1. Working Shifts:	04 shifts (0000-0600; 0600-1200; 1200-1800; 1800-2400)
3.2. Berths:	

Berth No.	Type	Length	Depth	Max DWT	Remarks
B.1A	Wharf	115m	-10.0m	30,000	General cargo
B.1B	Wharf	115m	-10.0m	30,000	General cargo
B.1C	Wharf	120m	-10.0m	30,000	General cargo
B.2	Jetty Pier	152	-9.0m	20,000	General cargo
B.3	Jetty Pier	152	-9.0m	10,000	General cargo
B.4	Wharf	200m	-8.50m	63,550	General cargo
B.5	Wharf	200m	-9.50m	50,000	Container

3.3. Storage Facilities:

Total port area: 306,568 m², of which:
Warehouse/shed: 20,960m². Open storage: 201,000 m². Tank: 12,000 m³.
Total storage capacity: 200,000mts, including 48,000 m² for stacking containers.

4.Services:

- 4.1. Garbage Dumping:
- 4.2. Fresh Water:
- 4.3. Bunker:
- 4.4. Workshop:

Compulsory. Every 02 days.
Available. Supplied by pipeline or motorboat.
Available. Order must be placed 03 days in advance.
Only minor repair work available.

5.Other information:

5.1. Berthing Priority:

1. Container feeders
2. Vessels with Despatch Agreement signed between Shippers/ Cnee and Quinhon Port
3. Each Shippers/ Cnee can have only one vessel at berth at one time.
4. Vessel with earlier Notice of Arrival (at least 7 days in advance).

5.2. Vessel Gears:

Shorecrane charge is very high. Vessel derricks/ cranes should be in good conditions.



Thanks & Best Regards

Dang Tuan Long (Mr.)/ General Director
HP: +84 983 403 859

MINH LONG MARITIME SERVICES CO.,LTD

Address: R.702, 7th Floor, Tower B, TD Plaza Building, Lot 20A Le Hong Phong Str, Gia Vien ward, Hai Phong City, Viet Nam

Tel: +84 2253 836 964 | Fax: +84 2253 836 965

Email: agency@minhlongmsc.com

Private: longdt@minhlongmsc.com & minhlongmsc@gmail.com

Skype: long.falcon

Website: <http://www.minhlongmsc.com>